TOWN OF ANTRIM P.O. Box 517 – Antrim, NH 03440 HIGHWAY DEPARTMENT – 588-2611 PERMIT TO BUILD DRIVEWAY ON TOWN ROAD

DA	ATE:				
N/	AME:	TAX MAP:	LOT#	:	
ΑI	DDRESS:				
PF	HONE #:E-MAIL:				
A	DRAWING OF THE PROPERTY SHOWING THE LOODELINEATION STAKES M) DRIVI	E WAY '	WITH
TY	YPE OF ROAD: Class VClass VIState	Private			
IF	THE PROPOSED DRIVEWAY IS ON A STATE HIGHWAY:				
	Yes No Has a NHDOT driveway permit been applied f	For and approved?			
of a proj	TE: Maintenance for all driveways shall be the responsibility my culverts and ditch line areas within three (3) feet of culver per unobstructed storm water flow though the culvert, per RS of following standards apply to all new and reconstructed drive Antrim. Please see the Antrim Subdivision and Site Plan Rev.	ert inlet and outlet pipes, keeping A 236:13. ways (including alteration to any	g areas f	Free of d	ebris fo
SP	ECIFICATIONS FOR ALL DRIVEWAYS		YES	NO	NA
1.	Residential driveways shall have a minimum width at the proper	ty line of 20 feet.			
2.	Residential driveways shall have a paved or processed gravel appropriate foot-wide radius for the first 12 feet in from the traveled edge of				
3.	Non-residential driveways shall have a paved or processed grave 30-foot-wide radius for the first 25 feet in from the traveled edge				
4.	All driveways shall have a minimum travel width of 14 feet.				
5.	All driveways shall have at least 13 ½ feet of year-round vertical	clearance.			
6.	The minimum distance from intersections or another driveway sand 150 feet in rural areas.	shall be 50 feet in residential areas			
7.	The centerline of the driveway must be a minimum of 14 feet from	om side or rear property lines.			
8.	There shall be a minimum sight distance of 200 feet in each direct of 3'9" off the ground up to standard height clearance of 13'6" u roadway edge.				
9.	Driveways shall intersect roadways at an angle of ninety (90) radius.	degrees, and must have a 25-foot			
NC	OTES:				

SPECIFICATIONS FOR ALL DRIVEWAYS (Cont.)			NA
O. All culverts shall be a minimum of twelve (12) inches in diameter and must be designed, installed, and maintained so as to support the heaviest vehicle likely to operate on the driveway. The Road Agent must approve all culvert diameters and proposed pitch for driveway culvert installations.			
11. Driveways that slope down from a road must be designed with proper crowning so as to pitch runoff to the shoulders and drainage of the driveway.			
12. All Driveways shall be designed to have at least a 2% slope /back pitch away from the road edge, and shall be installed with a minimal proper crown of the same degree of slope, from the center of the approach to the edges of the traveled way to allow for proper shedding of water off of travel way surface.			
NOTES:			
13. Shared Driveways:			
 a. An easement must be provided that addresses the rights of all property owners sharing the driveway. 			
14. Temporary Access:			
 Permits are required for temporary driveways for such activities as logging, utility maintenance and construction. The applicant must provide the Road Agent with site-specific information regarding road edge stabilization/protection, use of temporary culvert(s) if needed. 			
 Upon completion of the activity, the site shall be returned to its original condition, to the extent feasible. 			
c. A permit is valid for a maximum of 180 days from the date of approval. The Road Agent may grant an extension of up to 180 days for good cause shown.			
ADDITIONAL COMMENTS:			
DOAD ACENIT ADDDOVAL EOD THE CUDD CUT CULVEDT SIZE AND CULVEDT LOCATIO	NI NI		
ROAD AGENT APPROVAL FOR THE CURB CUT, CULVERT SIZE AND CULVERT LOCATION Road Agent:			
ROAD AGENT FINAL APPROVAL			
Road Agent:Date:			
CERTIFICATION BY THE BUILDING INSPECTOR THAT THE DRIVEWAY HAS BEEN INSTOTHE TOWN'S ORDINANCES AND REGULATIONS (Required before issuing a certificate of occupancy)	FALLE	D ACCO	RDING
Building Inspector:Date:			
Property owner: Date:			